DS-D60C-B
Digital Signage Player

- Variable Materials Supports static and dynamic materials, including the application, pictures, audio, video, PDF, streaming media, webpage, live video, third-party data, etc.

- Flexible Program Schedule   Supports free schedule and district display of multiple materials.   Supports variable display modes: display by day, display by week, custom display, etc.

- Centralized Management Remotely control and manage one or more screens, such as timed startup/shutdown, timed brightness/volume, and screenshot previewing.

- Organization Feature 5-level organization is available for managing materials, programs, terminals, and users.

- Multilevel User Permission Supports creating custom users, and allocating permission for users according to user level.

- Multiple Security Safeguards   3-level check of materials, programs, and schedules to prevent mistake release. Screensaver to secure safe for broadcast contents.   Encryption of data storage and transmission to avoid data tampering.

- Arbitrary Direction Remote Control The remote control, adopting wireless communication in 433 MHz, can control the information distribution box in arbitrary direction.

▪ Specification

Model		DS-D60C-B
Default Parameters	Material	DAT, MPG, VOB, TS, AVI, MKV, MP4, MOV, 3GP, FLV, WEBM, WMV, ASF, MP1, MP2, MP3, WMA, WAV, OGG, OGA, FLAC, ACC, M4A, XMF, MXMF, RTTTL, RTX, OTA, IMY, JPG, JPEG, BMP, GIF, PNG
Cabinet	Resolution	1920 × 1080p @ 30Hz, 1920 × 1080p @ 50Hz, 1920 × 1080p @ 60Hz, 1280 × 720p @ 30Hz, 1280 × 720p @ 50Hz, 1280 × 720p @ 60Hz, 3840 × 2160p @ 30Hz, 3840 × 2160p @ 50Hz, 3840 × 2160p @ 50Hz (YCbCr420), 3840 × 2160p @ 60Hz, 3840 × 2160p @ 50Hz (YCbCr420)
Built-in System	Operation System	Android 6.0.1
	CPU	4-core Cortex-A17
	Memory	2 GB
	Graphics	Mali T764
	Storage	8 GB (EMMC), TF Card 32 GB,TF Card Slot × 1
	CPU Chip	RK 3288
Interface	Video & Audio Input	1 x Audio In
	Video & Audio Output	1 × Audio Out， 1 × HDMI
	Network Interface	1 × LAN , 1000 M/100 M self-adaptive, Wi-Fi 802.11b/g/n
	Data Transmission Interface	2 × USB 2.0 interface, Bluetooth 4.0
Power	Power Supply	12 VAC, 2 A
	Standby Consumption	≤ 1 W
Working Environment	Working Temperature	0 °C to 50 °C (32 °F to 122 °F)
General	Product Dimensions (W × H × D)	145 mm × 145 mm × 31.89 mm (5.7" × 5.7" × 1.3")
	Working humidity	10 % to 90 %
	Package Dimensions (W × H × D)	188 mm × 176 mm × 101 mm (7.4" × 6.9" × 4.0")
	Net Weight	0.6 kg (1.3 lb.)
	Gross Weight	0.65 kg (1.4 lb.)
	Packing List	1 × Power Adaptor, 1× Remote Control, 1 × CD-ROM

▪ **Available Model**
DS-D60C-B

Distributed by

Headquarters
No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 (216)521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Korea
T +82-(0)31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com