

Junction Box

# HP 80-L



## HP 80-L

**Junction Box**

Productnumber: 32298001

Dimensions: 85 x 85 x 42 mm

Junction Box, with protection class IP55, Nominal cross-section 2.5 mm<sup>2</sup>, Ui=400V AC, certified according to VDE (DIN EN 60670-1/-22 (VDE 0606-1/-22)), Stepped nipple, M20, Sealing area 5 - 16 mm, (1 Rear, 7 Side), Internal fastening points, for standard indoor installations

**grey, without terminals**



## Technical Data

### electrical characteristics

Rated insulation voltage AC:	400 V
Max. conductor cross section:	2,5 mm <sup>2</sup>
Protection class:	II
Type of protection:	IP55
UL Type Rating:	not specified

### Colours

Base unit colour:	grey
Cover colour:	grey

### Dimensions

Width:	85 mm
Length:	85 mm
Height:	42 mm
Inner length:	78 mm
Inner width:	78 mm
Inner height:	38 mm

### Material characteristics

suitable for exterior use:	no
Industry quality:	no
Halogen free:	no

### mechanical properties

for sealing range max:	16 mm
Type of fastening:	Wall/ceiling mounting
Impact strength:	IK07
Sealable:	no
for sealing range min:	5 mm

## Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-25 °C
Max. ambient temperature:	40 °C
24h ambient temperature:	35 °C

## Material

Base unit material:	Polypropylene
Cover material:	Polypropylene

## Certificates

Test mark:	VDE (DIN EN 60670-1/-22 (VDE 0606-1/-22))
------------	---

## Accessories

[22742001 - KVR M20-MGM - Cable gland](#)

[22742101 - KVR M20-GDB/MGM - Cable gland](#)

[26012001 - DMS M20/w - Double-membrane seals](#)

[26042001 - DMS M20 - Double-membrane seals](#)

[84000401 - Abox 025/040 KLS-2.5<sup>2</sup>/4<sup>2</sup> - Terminal block](#)

## Cable gland

