

THC-T280



- 8 MP turret camera
- EXIR 2.0: advanced infrared technology with 60 m IR distance
- Water and dust resistant (IP67)
- 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS).

▪ Specification

Model	THC-T280	
Camera	Image Sensor	8.29 MP CMOS
	Max. Resolution	3840 (H) × 2160 (V)
	Min. Illumination	0.01 Lux@(F1.2, AGC ON), 0 Lux with IR
	Shutter Time	PAL: 1/12.5 s to 1/50, 000 s NTSC: 1/15 s to 1/50, 000 s
	Day & Night	ICR
	Angle Adjustment	Pan: 0 to 360°, Tilt: 0 to 75°, Rotation: 0 to 360°
	Signal System	PAL/NTSC
Lens	Lens Type	2.8 mm, 3.6 mm, 6 mm fixed lens
	Focal Length & FOV	102.9° (2.8 mm), 79° (3.6 mm), 44.7° (6 mm)
	Lens Mount	M12
Image	Image Parameters Switch	STD/HIGH-SAT
	Image Settings	Brightness, Sharpness, Smart IR
	Frame Rate	TVI: 8MP@12.5fps, 8MP@15fps, 4MP@25fps, 4MP@30fps, 2MP@25fps, 2MP@30fps AHD: 8MP@15fps CVI: 8MP@12.5fps, 8MP@15fps CVBS: PAL/NTSC
	Day/Night Mode	Auto/Color/BW (Black and White)
	Wide Dynamic Range (WDR)	Digital WDR
	Image Enhancement	BLC, HLC
	White Balance	Auto/Manual
	AGC	Yes
Interface	Video Output	Switchable TVI/AHD/CVI/CVBS
General	Material	Enclosure: Plastic Main body: Metal
	Dimension	∅ 109.82 mm × 91.03 mm (4.32" × 3.6")
	Weight	Approx. 315 g (0.69 lb.)
	Operating Condition	-40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation)
	Communication	HIKVISION-C
	Language	English
	Power Supply	12 VDC ± 25% *You are recommended to use one power adapter to supply the power for one camera.

	Consumption	Max. 2.9 W
	IR Range	Up to 60 m

▪ Available Model

THC-T280(2.8mm)(Hilook UK),THC-T280(3.6mm)(Hilook UK),

